

SL900

GNSS Receiver



The SL900 is a high-precision GNSS receiver that performs even under the most demanding conditions. With its features, the SL900 is capable of delivering highly accurate data in real-time to any devices via a Bluetooth connection. Compact and lightweight, this GNSS receiver is one of the most flexible solutions that promises positioning reliability.



Swedish
Quality



Tilt
Compensator



Multi-Constellation
Tracking



Bluetooth



Long
Battery Life



Windows
Compatibility



Android
Compatibility



NFC
Module



Internet
RTK
Technology



PPK Mode

Tilt compensation solution

With surveyors in mind, Satlab designed a solution to increase efficiency in your workflow by cutting down time wasted from offsetting slanted measurements. With the tilt compensator, the SL900 can save up to 20 percent of time compared to conventional surveying practices. This solution allows you to focus on your surroundings conveniently while ensuring your safety and comfort.





Applications

- Monitoring
- Mapping
- Land Survey
- Topography and As-built
- Landfill
- Hydrographic
- Agriculture
- Sensor
- UAV Base Station

Efficient and dependable

Powered by advanced GNSS engine, this receiver offers precise positioning and advanced interference mitigation which performs even in the most remote or challenging environments. Using its 1408 channel tracking capabilities, it can track all current and upcoming signals, offering sub-metre to centimetre precise positioning with different modes (RTK, PPK, Static).

Advanced Technologies Inside


Equipped with the latest tilt compensation algorithm and built-in high-performance 9-axis Inertial Measurement Unit (IMU), the measurement for hard-to-reach points is simple but precise with the high-performance tilt survey. Quality results are guaranteed even if you lose the signal while under extreme circumstances with great anti-interference ability.

TECHNICAL SUPPORT


Satlab offers online resources and a professional support network available worldwide.




Multi-Constellation
Tracking



NFC
Technology



Data
Collector



Long
Operation Time



Professional
Support Network

SL900 GNSS Receiver

Data Specifications

GNSS

Signal Tracking¹

GPS (L1C/A, L1C, L2P(Y), L2C, L5)
GLONASS (L1, L2, L3)
BeiDou (B1I, B2I, B3I, B1C, B2a, B2b)
Galileo (E1, E5A, E5B, E6)
NavIC (L5)
QZSS (L1, L2, L5, L6*)
SBAS (L1, L2, L5)
PPP(B2b-PPP, Galileo E6-HAS)

No. of Channels

1408

POSITION PERFORMANCE²

High-Precision Static Static and Fast Static Post Processing Kinematic (PPK / Stop & Go)

H: 2.5mm + 0.1 ppm RMS / V: 3.5mm + 0.4 ppm RMS
H: 2.5mm + 0.5 ppm RMS / V: 5mm + 0.5 ppm RMS
H: 8mm + 1 ppm RMS / V: 15mm + 1 ppm RMS
Initialization time: Typically 10 min for base and 5 min for rover
Initialization reliability: Typically >99.9%

PPP

Code Differential GNSS Positioning

H: 10cm / V: 20cm
H: ±0.25m+1ppm RMS / V: ±0.5m+1ppm RMS
SBAS: 0.5m (H), 0.85m (V)

Real Time Kinematic (RTK)

H: 8mm+1ppm RMS / V: 15mm+1ppm RMS
Initialization time: Typically <10s
Initialization reliability: Typically > 99.9%

Positioning rate

1 Hz, 5 Hz and 10 Hz

Time to first Fix

Cold start: < 45s | Hot start: < 30s | Signal re-acquisition: < 2s

Hi-Fix³

H: RTK+10mm / minute RMS | V: RTK+20mm / minute RMS

Tilt Survey Performance⁴

Additional horizontal pole-tilt uncertainty typically less than 8mm+0.7mm/°tilt(0° ~ 60°)

COMMUNICATIONS

I/O Interface

Mini USB, TNC antenna port, DC power input(5-pin)
SIM card slot, TF card slot

Network Communication

Full band support for cellular mobile network
(LTE, WCDMA, GPRS, GSM)
GSM 900MHz&1800MHz, WCDMA 2100MHz/900MHz,
LTE Band 1,3,7,8,20

WiFi

Frequency 2.4GHz, Supports 802.11 b/g/n

Bluetooth

V2.1+EDR, 2.4GHz

NFC

Near Field Communication for device touch pairing

Internal UHF Radio

Power: 0.5W/1W/2W Adjustable
Frequency: 410MHz~470MHz | Channel: 116 (16 scalable)
Protocol: HI-TARGET, TRIMTALK450S, TRIMMARK III,
SATEL-3AS, TRANSEOT, etc.
Working Range: Typically 3~5km, optimal 8~15km

PHYSICAL

Dimensions (W x H)

170mm × 95mm

Weight

1.2kg including battery

Operation temperature

-40 °C to +65 °C

Storage temperature

-40 °C to +85 °C

Humidity

100% non-condensing

Water/dustproof

IP67 dustproof, protected from temporary immersion to depth of 1.0m (3.28ft)

Shock and vibration

MIL-STD-810G, 516.6

Free fall

Designed to survive a 2m(6.56ft) natural fall onto concrete

ELECTRICAL

Battery⁵

Internal 7.4V / 5000mAh lithium-ion rechargeable and removable battery

External power

RTK rover(UHF/Cellular): up to 18 hours
6V to 28V DC external power input(5-pin port)

CONTROL PANEL

Physical button

1

LED Lights

Satellite, Signal, Power

SYSTEM CONFIGURATION

Storage

8GB ROM internal storage

Output format

ASCII: NMEA-0183

Output rate

1Hz~20Hz

Static data format

GNS, Rinex

Real Time Kinematic (RTK)

RTCM2.X, RTCM3.X, CMR

Network Mode

VRS, FKP, MAC, Support NTRIP protocol



Headquarters:

Stora Ävägen 21, 436 34
ASKIM, Sweden

Regional Offices:

Budapest, Hungary
Ankara, Turkey
Dubai, UAE
New Delhi, India
Scottsdale, USA
Tokyo, Japan
Hong Kong, China

www.satlab.com.se



Note

1.QZSS L6 can be provided by firmware upgrade.

2.The measurement accuracy, precision, reliability and initialization time depend on various factors, including tilt angle, number of satellites, geometric distribution, observation time, atmospheric conditions and multi-path validation, etc. The data are derived under normal conditions.

3.Accuracies are dependent on GNSS satellite availability. Hi-Fix Positioning ends after 5 minutes without differential data. Hi-Fix is not available in all regions, check with your local sales representative for more information.

4.Irregular operations such as rapid rotation and high-intensity vibration may affect the inertial navigation accuracy.

5.The battery operating time is related to the operating environment, operating temperature and battery life.

Descriptions and Specifications are subject to change without notice.